



12 Metre 3 bar fixed cultivator, set up for sowing wheat into wet conditions at Pampas QLD



12 Metre fixed bar cultivator at Mallowa NSW



Boss Lilliston Rigs feature bolted adjustments making in field set ups easy with consistent results



2 x 12 Metre Lilliston rigs being assembled at Boss

Fixed Bar Cultivator

Boss fixed bar cultivators are available in a variety of widths & tyne configurations to suit most applications.

Frames can be fabricated in 4" or 6" RHS depending on the tynes you require and can be folding or rigid with depth gauge wheel and stabiliser kits fitted as required.

Features & Specifications:

- Tough 2 or 3 Bar, 4" or 6" heavy wall RHS frames.
- Cat 3/Cat4 linkage standard
- Diamond mounted tyne assemblies for reduced twist and easy toolbar relocation
- Straight line shear assembly used on tynes utilising a standard 1/2" or 5/8" bolt for cost effective long term performance
- 3" x 1" shanks or fabricated shanks can be fitted with friction trips or spear points as required
- Ezy shank height adjustment for simple one handed adjustment
- Solid fertiliser or gas boots available
- Furrowers or low crown Alabamas available
- Optional heavy duty stabiliser with 4 tonne hubs, 30" x 10mm disc with independent adjustment and vertical fold
- Australian Manufactured

Lilliston Rig

Available in 8 row & 12 row our lilliston rigs or rolling cultivators as they are also known are designed to handle a variety of tasks in the field:

- Refine seed beds prior to planting for added seedling vigour & improved water infiltration
- Incorporate pre- and post-emergence chemicals for fast knockdown and effective weed control
- Cultivation of weeds while preserving seedling growth and crop root systems
- Help control soil and water losses from erosion whilst improving soil aeration
- Help manage residue retention
- The Boss lilliston rig also features new bolted gang adjustments so in field set ups are made evenly & are simple for operators to perform

Features & Specifications:

- Tough 7" heavy wall RHS frames with bridge beams
- Cat 3/Cat4 linkage standard
- Heavy duty bolted cross-members used throughout
- Hard faced 5 spider gangs with simple to use bolted adjustments
- Straight line shear release clamps & shanks fitted with Alabamas & utilising a standard 1/2" shear bolt for cost effective long term performance
- Optional heavy duty stabiliser with 4 tonne hubs, 30" x 10mm disc with independent adjustment and vertical fold
- All pivots use our proven durable poly bushes and 1 1/4" chrome/stainless steel pins
- Australian Manufactured



BOSS AGRICULTURE

A division of Boss Engineering Pty Ltd

www.bosseng.com.au
www.bossagparts.com.au

40 Taylor Avenue Inverell NSW

Phone **02 6721 2677**

Fax 02 6721 2760

Dan Ryan **0488 512 677**

Dave Herbert (Dalby QLD) **0439 286 277**